

	Description	Descrizione	Family Famiglia	Page Pagina
	For electrovalves, EN175301-803 style A, ISO 4400, (former DIN 43650-A), 18 mm spacing, 2p+2G, female, with cable	<i>Per elettrovalvole, EN175301-803 stile A, ISO 4400, (ex DIN 43650-B), interasse 18 mm, 2p+2T, femmina, con cavo</i>	CA	45-2
	For electrovalves, EN175301-803 style A, ISO 4400, (former DIN 43650-A), 18 mm spacing, 3p+G, female, with cable	<i>Per elettrovalvole, EN175301-803 stile A, ISO 4400, (ex DIN 43650-A), interasse 18 mm, 3p+T, femmina, con cavo</i>	CC	45-4
	For electrovalves, style B-industrial, 11 mm spacing, 2p+G, female, with cable	<i>Per elettrovalvole, stile B-industriale, interasse 11 mm, 2p+T, femmina, con cavo</i>	CE	45-6
	For electrovalves, EN175301-803 style B, ISO 6952, (former DIN 43650-B), 10 mm spacing, 2p+G, female, with cable	<i>Per elettrovalvole, EN175301-803 stile B, ISO 6952, (ex DIN 43650-B), interasse 10 mm, 2p+T, femmina, con cavo</i>	CF	45-8
	For electrovalves, EN175301-803 style C, ISO 15217, (former DIN 43650-C), 8 mm spacing, 2p or 3 + G, female, with cable	<i>Per elettrovalvole, EN175301-803 stile C, ISO 15217, (ex DIN 43650-C), interasse 8 mm, 2p o 3p + T, femmina, con cavo</i>	CL	45-10
	For electrovalves, style C-industrial, 9.4 mm spacing, 2p or 3p + G, female, with cable	<i>Per elettrovalvole, stile C-industriale, interasse 9.4 mm 2p o 3p + T, femmina, con cavo</i>	CN	45-12
	For electrovalves, EN175301-803 style A, ISO 4400, (former DIN 43650-A), 18 mm spacing, current amplifier with cable	<i>Per elettrovalvole, EN175301-803 stile A, ISO 4400, (ex DIN 43650-A), interasse 18 mm, amplificatore corrente con cavo</i>	C special	45-14
	For electrovalves, EN175301-803 style A, ISO 4400, (former DIN 43650-A), 18 mm spacing, up to 3p+G, female, with screw terminals	<i>Per elettrovalvole, EN175301-803 stile A, ISO 4400, (ex DIN 43650-A), interasse 18 mm, fino a 3p+T, femmina, con terminali a vite</i>	VC	45-16
	For electrovalves, style B-industrial, 11 mm spacing, 2p+G, female, with screw terminals	<i>Per elettrovalvole, stile B-industriale, interasse 11 mm, 2p+T, femmina, con terminali a vite</i>	VE	45-20
	For electrovalves, EN175301-803 style B, ISO 6952, (former DIN 43650-B), 10 mm spacing, 2p+G, female, with screw terminals	<i>Per elettrovalvole, EN175301-803 stile B, ISO 6952, (ex DIN 43650-B), interasse 10 mm, 2p+T, femmina, con terminali a vite</i>	VF	45-22

	Description	Descrizione	Family Famiglia	Page Pagina
	For electrovalves, EN175301-803 style C, (former DIN 43650-C), ISO 15217, 8 mm spacing, 2p or 3p + G, female, with screw terminals	Per elettrovalvole, EN175301-803 stile C, (ex DIN 43650-C), ISO 15217, interasse 8 mm, 2p o 3p + T, femmina, con terminali a vite	VL	45-24
	For electrovalves, style C-industrial, 9.4 mm spacing, 2p or 3p + G, female, field attachable	Per elettrovalvole, stile C-industriale, interasse 9.4 mm, 2p o 3p + T, femmina, a cablare	VN	45-26
	For electrovalves, up to 3p+G, males, soldering	Per elettrovalvole, fino a 3p+T, maschi, a saldare	VP VR VT VU	45-28
	7/8" straight, female or male contacts, female or male threads, from 2 to 14 poles, with cable	7/8" diritto, contatti femmina o maschio, filettature femmina o maschio, da 2 a 14 poli, con cavo	HDL	45-30
	7/8" straight, female or male contacts, female or male threads, from 2 to 14 poles, with shielded cable	7/8" diritto, contatti femmina o maschio, filettature femmina o maschio, da 2 a 14 poli, con cavo schermato	HDL	45-32
	7/8" angled, female or male contacts, female or male threads, from 2 to 14 poles, with cable	7/8" angolato, contatti femmina o maschio, filettature femmina o maschio, da 2 a 14 poli, con cavo	HDM	45-34
	7/8" receptacle, front mounting, female or male contacts, female or male threads, from 2 to 14 poles, with wires	7/8" pannello, montaggio frontale, contatti femmina o maschio, filettature femmina o maschio, da 2 a 14 poli, con fili	HDE	45-36
	7/8" receptacle, rear mounting, female or male contacts, female or male threads, from 2 to 14 poles, with wires	7/8" pannello, montaggio da dietro, contatti femmina o maschio, filettature femmina o maschio, da 2 a 14 poli, con fili	HDS	45-38
	D-Sub series, from 2 to 62 poles, with cable	Serie Sub-D, da 2 a 62 poli, con cavo	J	45-40

	Description	Descrizione	Family Famiglia	Page Pagina
	M12 or 1/2" straight, coding A or coding C, from 4 to 12 poles, field attachable	M12 o 1/2" diritto, codifica A o codifica C, da 4 a 12 poli, da assemblare	RDJ	45-42
	M12 or 1/2" angled, coding A or coding C, from 4 to 12 poles, field attachable	M12 o 1/2" angolato, codifica A o codifica C, da 4 a 12 poli, da assemblare	RDK	45-43
	M12 straight, coding A, from 2 to 12 poles, with cable	M12 diritto, codifica A, da 2 a 12 poli, con cavo	RDL	45-44
	M12 straight, coding A, from 2 to 12 poles, with shielded cable	M12 diritto, codifica A, da 2 a 12 poli, con cavo schermato	RDL	45-46
	M12 angled, coding A, from 2 to 12 poles, with cable	M12 angolato, codifica A, da 2 a 12 poli, con cavo	RDM	45-48
	M12 angled, coding A, from 2 to 12 poles, with shielded cable	M12 angolato, codifica A, da 2 a 12 poli, con cavo schermato	RDM	45-50
	M12 receptacle, front mounting, coding A, from 2 to 12 poles, with wires or to solder	M12 pannello, montaggio frontale, codifica A, da 2 a 12 poli, con fili o a saldare	RDE	45-52
	M12 receptacle, rear mounting, coding A, from 2 to 12 poles, with wires or to solder	M12 pannello, montaggio da dietro, codifica A, da 2 a 12 poli, con fili o a saldare	RDS	45-56
	M8 straight, from 3 to 4 poles, field attachable	M8 diritto, da 3 a 4 poli, da assemblare	REJ	45-60
	M8 angled, from 3 to 4 poles, field attachable	M8 angolato, da 3 a 4 poli, da assemblare	REK	45-61

	Description	Descrizione	Family Famiglia	Page Pagina
	M8 straight, from 2 to 5 poles, with cable	<i>M8 diritto, da 2 a 5 poli, con cavo</i>	REL	45-62
	M8 angled, from 2 to 5 poles, with cable	<i>M8 angolato, da 2 a 5 poli, con cavo</i>	REM	45-64
	M8 straight, from 2 to 5 poles, snap in, with cable	<i>M8 diritto, da 2 a 5 poli, snap in, con cavo</i>	REN	45-66
	M8 angled, from 2 to 5 poles, snap in, with cable	<i>M8 angolato, da 2 a 5 poli, snap in, con cavo,</i>	REQ	45-68
	M8 receptacle, front mounting, from 2 to 5 poles, with wires or to solder	<i>M8 pannello, montaggio frontale, da 2 a 5 poli, con fili o a saldare</i>	REE	45-70
	M8 receptacle, rear mounting, from 2 to 5 poles, with wires or to solder	<i>M8 pannello, montaggio da dietro, da 2 a 5 poli, con fili o a saldare</i>	RES	45-74
	M12 or 1/2" straight, coding C, dual key, from 3 to 6 poles, with cable	<i>M12 o 1/2" diritto, codifica C, doppia chiave, da 3 a 6 poli, con cavo</i>	RCL	45-164
	M12 or 1/2" angled, coding C, dual key, from 3 to 6 poles, with cable	<i>M12 o 1/2" angolato, codifica C, doppia chiave, da 3 a 6 poli, con cavo</i>	RCM	45-166
	Accessories & Circuit variants for connectors	<i>Accessori &amp; Varianti circuito per connettori</i>		46-2