






VF



- Connettore rettangolare stile B
- Materiale rivestimento: PA66 30%GF

- Rectangular connector style B
- Coating material: PA66 30%GF

without electronic components senza componenti elettronici	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	02A00	1.250	1.250	10	--
varistor varistore	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max a @40°	Clamping voltage Tensione intervento V
	04A10	1..18	1..14	10	22..43
	04A20	1..38	1..30		47..93
	04A40	1..80	1..60		100..165
	04A60	1..170	1..130		205..340
	04A90	1..250	1..250		350..710
parallel diode diodo parallelo	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	1A	05A00	--	10	-1
	3A	05K00			
R-C group filter: 100 ohm resistor 100nF/275Vac capacitor filtro gruppo R-C: resistenza 100 ohm, condens. 100nF/275Vca	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	51A00	--	1.250	10	--
transil parallel 600W transil parallelo 600W	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	59A20	1..28	1..24	10	33..59
	59C20	1..36	1..25		37..70
	59C40	1..80	1..55		100..178
	59C60	1..170	1..120		200..353
	59C90	1..250	1..250		400..710