






CL



2P / 2P+PE

- Connettore micro stile C
- Con elettronica e Led segnalazione
- Materiale rivestimento: **POLIURETANO TRASPARENTE**

- Rectangular connector style C
- With electronics and signalling Led
- Coating material: **TRANSPARENT POLYURETHANE**

red led led rosso	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	19A3R	10..50	10..50	6	--
	19A8R	70..250	70..250		
red Led + diode Led rosso + diodo	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	1A	24A3R	10..50	6	-1
		24A8R	70..250		
	3A	28A3R	10..50		
		28A8R	70..250		
red Led + diode in series Led rosso + diodo in serie	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	1A	31K3R	10..50	1	--
		31K8R	70..250		
	3A	32K3R	10..50		
red Led + transil 600 W Led rosso + transil 600W	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	65A2R	10...28	10...24	6	33..59
	65C2R	10...36	10...25		37..70
	65C4R	10..80	10..55		100..178
	65C6R	70..170	70..120		200..353
	65C9R	70..250	70..250		400..710
red Led + R-C group filter, 100 ohm resistor, 100nF/275Vac capacitor Led rosso + filtro gruppo R-C, resistenza 100ohm, condens. 100nF/275Vca	COD.:	Voltage Tensione Vdc:	Voltage Tensione Vac:	max current corrente max A @40°	Clamping voltage Tensione intervento V
	73A3R	--	10..50	6	--
	73A8R	--	70..250	6	--